

FreeStyle Air Max



The FreeStyle Air arrives ready to take its place as a lightweight accessory that integrates seamlessly with existing FreeStyle systems. Compatible with FreeStyle mounts, extension cables and LED-140 & LED-150 Series controllers, this portable thin profile panel offers the advantages of easy deployment and favorable cost of ownership to current FreeStyle owners and operators.

In addition to a twist-on mount for light stands, and corner bumpers for 4-point hangs, the FreeStyle Air comes with eyelets to simplify overhead and other surface attachment. Its rigid construction prevents any flex when handling and safeguards the integrity of its components. Usable LED life is extended with a proven passively-cooled design that ensures color and luminosity remain stable over the rated life of the LEDs.

Ease of maintenance is built into a user serviceable design. It features a removable upper rail and quick access to pull-out LED platens that are easily replaced or repaired. Combining new mobility and reliable performance with familiar features, the FreeStyle Air delivers Kino Flo's renowned Color Science LED technology in this lightweight addition to the range.

Features

- Kelvin presets & custom settings, 2500K-9900K
- Dimming without color shift
- Green/Magenta control
- Dial in any color through Hue Angle and Saturation control
- Kino Flo presets and Gels
- RGB, CIE xy, FX (Effects) control
- Camera Profiles (LUTs), Color Space
- Manual & DMX Dimming, DMX wireless (Lumen Radio)

Kinoflo.com

Photometrics

6500 Kelvin												
Feet	2	4	6	8	10	12	14	16	18	20		
Foot Candles	978	320	152	88	57	40	30	24	19	15		
Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5	5.5	6
Lux	14100	4950	2360	1380	910	631	472	366	294	240	201	172

Specifications

Fixture Specifications

- Kelvin Range: 2500~9900
- Dimming Range: 100%~1%
- IP Rating: IP20
- Dimensions: 39.5 x 2 x 22" (100 x 5 x 56cm)
- Weight: 7.5 lb (3Kg)

Controller Specifications

- Controller: LED-140X
- Input Voltage VAC: 100~240VAC, 50/60Hz, 150W
- Amps VAC: 1.25A at 120VAC, 0.65A at 230VAC
- Input Voltage VDC: 18~36VDC, 150W
- Amps VDC: 6.25A at 24VDC
- Kelvin Range: 2500~9900
- Dimming Range: 100%~1%
- Dimensions: 9.5 x 7.5 x 2.5" (24 x 19 x 6.5cm)
- Weight: 4.5 lb (2Kg)

Accessories

- PAN-AMAX- FreeStyle Air Max Panel w/ Harness
- LED-140X-120U - FreeStyle 140 LED DMX Controller, Univ 120U
- LED-140X-230U - FreeStyle 140 LED DMX Controller, Univ 230U
- MTP-BG41 - KinoGrip 41K Mount w/ Baby Receiver (16mm)
- X12-F425 - FreeStyle/4 Extension, 25ft

