

VELVET Light

THE ROBUST LED PANELS PIONEERS



NATURAL
VELVET BEAUTY LIGHT

ROBUST 100% Aluminum body & SILENT Fan free operation

IT IS SOFT, IT IS
VELVET

THE REAL POWER ON SOFT PANELS

VELVET 2x2 LIGHT

VELVET LIGHT 2x2 is the most cost effective, simple to install and versatile to operate soft & space light available



POWERFUL

Its big square surface produce more output than a tungsten spacelight 5Kw drawing just 290W without maintenance.

100% SILENT

THELIGHT state of the art passive cooling technology keep LED in the optimum temperature to last beyond 50.000 hours without noisy fans.

QUICK & EASY

The bi-color slim panel (7cms thick) doubles a 5Kw tungsten + light bank being much easier to install.

VELVET Light ADVANTAGES

VELVET LIGHT 1 RAINPROOF VELVET LIGHT 2 RAINPROOF VELVET LIGHT 2x2 VELVET LIGHT 4



- ▶ shock resistant 100% aluminum body
- ▶ quick set up and adjustment
- ▶ 50% more light output with the best quality Osram LED
- ▶ completely silent fan free operation
- ▶ more than bi-colour 2700 to 6500 K
- ▶ digital display with shock resistant buttons
- ▶ perfect color rendition & consistency lamp to lamp
- ▶ bi-directional DMX RDM dual XLR-5 connectors (Studio version)
- ▶ affordable European quality with 2 years warranty
- ▶ 100% made & designed in Barcelona (Spain)

VELVET Light 1&2 exclusive BENEFITS

- ▶ rainproof IP54
- ▶ Vlock or Gold battery mount



THE INCREDIBLY SOFT BEAM PANELS

VELVET 4 LIGHT

NATURAL SOFT LIGHT

Incredibly soft and wraparound quality light to easily get beauty shots and natural portraits. VELVET Light 4 is so efficient to deliver 1000 Lux of soft light at 3 meters drawing only 290W.

The natural soft beam is very easy to use, produce no shadows on the actors faces and does no disturb their eyes. The light evenness and power make VELVET Light the right choice on lighting backgrounds, as space light and invaluable on location as all purpose fixture.



READY TO RIG

With a wide range of rigging options: Yoke with ergonomic just one hand tilt lock, ball head rapid mounts, 1/4-20" threads for rigging are located on top and bottom of every VELVET panel.



THELIGHT
info@thelight.com.es



Intellectual Property

THELIGHT VELVET Light technology is protected under spanish patents and international patents pending
2016 © Copyright THELIGHT. All rights reserved.

RAINPROOF SOFT LED PANELS **VELVET 1** LIGHT

Rainproof **VELVET LIGHT 1 & 2** are the most rugged portable lights designed to instantly setup & adjust using shock resistant buttons



VELVET NATURAL SOFT LIGHT

Incredibly soft and wraparound VELVET quality light to easily get beauty shots and natural portraits

QUICK SET UP

User friendly digital display with shock-resistant buttons. Yoke with ergonomic just one hand tilt lock knob.



STUDIO SERIES ADVANTAGES **VELVET 1&2** LIGHT LIGHT



ADVANCED DMX MASTER/SLAVE

DMX remote control even without a controller! With the Master-Slave function you can link several units and operate without a console. The Master will be the controller for the other units.

BI-DIRECTIONAL DMX RDM

The perfect solution on Studio simplifying the assignment and channel addressing of every fixture.



THE VELVET TOUCH

VELVET Light is the all-rounder for every shooting on location or studio. Strong, thin and versatile. VELVET can be powered with any battery or AC worldwide. VELVET panels are designed to be easily rigged and instantly adjusted to match any ambient light and to produce a natural light effect.



VELVET Light SERIES

TECHNICAL SPECIFICATIONS

VELVET Light 1	VELVET Light 1 STUDIO	VELVET Light 2	VELVET Light 2 STUDIO	VELVET Light 4	VELVET Light 2x2
RAINPROOF IP54	DUSTPROOF	RAINPROOF IP54	DUSTPROOF	DUSTPROOF	DUSTPROOF
DIMENSIONS 370 x 308 x 68mm WEIGHT 3,5 Kg	DIMENSIONS 370 x 308 x 68mm WEIGHT 3,5 Kg	DIMENSIONS 670 x 308 x 68mm WEIGHT 6 Kg	DIMENSIONS 670 x 308 x 68mm WEIGHT 6 Kg	DIMENSIONS 1250 x 308 x 68mm WEIGHT 11 Kg	DIMENSIONS 670 x 620 x 68mm WEIGHT 12Kg
POWER DRAW 75W 0,68 Ah at 110 VAC	POWER DRAW 75W 0,68 Ah at 110 VAC	POWER DRAW 150W 1,36 Ah at 110 VAC	POWER DRAW 150W 1,36 Ah at 110 VAC	POWER DRAW 290W 2,63 Ah at 110 VAC	POWER DRAW 290W 2,63 Ah at 110 VAC
XLR-3 POWER SUPPLY 12-35 V DC 90-264V AC 50/60Hz	XLR-3 POWER SUPPLY 12-35 V DC 90-264V AC 50/60Hz	XLR-3 POWER SUPPLY 24-35 V DC 90-264V AC 50/60Hz	XLR-3 POWER SUPPLY 24-35 V DC 90-264V AC 50/60Hz	XLR-3 POWER SUPPLY 26-28 V DC 90-264V AC 50/60Hz	XLR-3 POWER SUPPLY 26-28 V DC 90-264V AC 50/60Hz
XLR-5 x 1 IN / OUT DMX-RDM	XLR-5 x 2 IN / OUT DMX-RDM	XLR-5 x 1 IN / OUT DMX-RDM	XLR-5 x 2 IN / OUT DMX-RDM	XLR-5 x 2 IN / OUT DMX-RDM	XLR-5 x 2 IN / OUT DMX-RDM
BATTERY OPERATED V-LOCK / GOLD		BATTERY OPERATED V-LOCK / GOLD		BATTERY OPERATED POWER STATION Through XLR3	BATTERY OPERATED POWER STATION Through XLR3

COLOUR TEMPERATURE Adjustable from 2700 K to 6500 K in 100 K increments

LIGHT INTENSITY Dimmable 0 to 100%

CRI & TLCI Over 90

BEAM ANGLE 100%

THELIGHT LED Rated life More than 50,000 hours

THELIGHT LED Technology OSRAM selected BIN LED Core unit + Optic diffuser + CPU software control

ACCESSORIES

Foldable Snapgrid, Snapbag diffuser, removable barndoors, center ball mount, yoke mount, PO yokes, AC power supply, Vlock or Gold mounts, cordura soft bag, hard case, remote control.

PHOTOMETRICS

VELVET Light 1	VELVET Light 1 STUDIO	VELVET Light 2	VELVET Light 2 STUDIO	VELVET Light 4	VELVET Light 2x2
1 meter / 3 feet 1700 Lux / 157 fc	1 meter / 3 feet 1700 Lux / 157 fc	1 meter / 3 feet 3600 Lux / 334 fc	1 meter / 3 feet 3600 Lux / 334 fc	1 meter / 3 feet 8000 Lux / 740 fc	1 meter / 3 feet 8000 Lux / 740 fc
3 meters / 10 feet 210 Lux / 19 fc	3 meters / 10 feet 210 Lux / 19 fc	3 meters / 10 feet 450 Lux / 42 fc	3 meters / 10 feet 450 Lux / 42 fc	3 meters / 10 feet 1000 Lux / 93 fc	3 meters / 10 feet 1000 Lux / 93 fc
				6 meters / 20 feet 320 Lux / 30 fc	6 meters / 20 feet 320 Lux / 30 fc



RAINPROOF IP54



PIONEERS ON PANELS MADE TO LAST

specifications subject to change without notice. THELIGHT technology is protected under Spanish License Laws with international patents pending

THE RUGGED & QUICK SOFT PANELS **VELVET 2** LIGHT

QUALITY WHITE LIGHT

Professional and consistent color rendition: With a CRI & TLCI over 90 to get perfect skin tones and real colors.

Absolutely consistent lamp to lamp to mix as many VELVET units as you wish to get exactly the same light quality and color reproduction.

MADE TO LAST

Robust 100% aluminum body, made to endure the toughest working conditions on any situation.

Using the best quality OSRAM LED, exclusive electronics and custom designed aluminum heat-sink we keep the LED in the optimum temperature to last 50,000 hours using no fans.

