FreeStyle Air Mini



The FreeStyle Air arrives ready to take its place as a lightweight accessory that integrates seamlessly with existing FreeStyle systems. Compatible with FreeStyle mounts, extension cables and LED-140 & LED-150 Series controllers, this portable thin profile panel offers the advantages of easy deployment and favorable cost of ownership to current FreeStyle owners and operators.

In addition to a twist-on mount for light stands, and corner bumpers for 4-point hangs, the FreeStyle Air comes with eyelets to simplify overhead and other surface attachment. Its rigid construction prevents any flex when handling and safeguards the integrity of its components. Usable LED life is extended with a proven passively-cooled design that ensures color and luminosity remain stable over the rated life of the LEDs.

Ease of maintenance is built into a user serviceable design. It features a removable upper rail and quick access to pull-out LED platens that are easily replaced or repaired. Combining new mobility and reliable performance with familiar features, the FreeStyle Air delivers Kino Flo's renowned Color Science LED technology in this lightweight addition to the range.

Features

- Kelvin presets & custom settings, 2500K-9900K
- · Dimming without color shift
- · Green/Magenta control
- Dial in any color through Hue Angle and Saturation control
- · Kino Flo presets and Gels
- RGB, CIE xy, FX (Effects) control
- Camera Profiles (LUTs), Color Space
- Manual & DMX Dimming, DMX wireless (Lumen Radio)

Photometrics

_													
	6500 Kelvin												
	Feet	2	4	6	8	10	12	14	16	18	20		
	Foot Candles	483	127	58	32	21	15	11	8	7	5		
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5	5.5	6
	Lux	7390	1970	912	520	334	233	171	132	105	86	71	60

Specifications

Fixture Specifications

Kelvin Range: 2500~9900Dimming Range: 100%~1%

· IP Rating: IP20

Dimensions: 21 x 2 x 13" (53 x 5 x 33cm)

· Weight: 3 lb (1Kg)

Controller Specifications

· Controller: LED-140X

Input Voltage VAC: 100~240VAC, 50/60Hz, 55W
Amps VAC: 1.25A at 120 VAC, 0.65A at 230VAC

- Input Voltage VDC: 18~36VDC, 150W

- Amps VDC: 6.25A at 24VDC

Kelvin Range: 2500~9900Dimming Range: 100%~1%

- Dimensions: 9.5 x 7.5 x 2.5" (24 x 19 x 6.5cm)

Weight: 4.5 lb (2Kg)

Accessories

- PAN-AMINI FreeStyle Air Mini Panel w/ Harness
- LED-140X-120U FreeStyle 140 LED DMX Controller, Univ 120U
- LED-140X-230U FreeStyle 140 LED DMX Controller, Univ 230U
- MTP-BG41S KinoGrip 41K Mount w/ Baby Receiver Short (16mm)
- · X12-F425 FreeStyle/4 Extension, 25ft



