



KINO FLO
Lighting Systems

celeb[®] LED



Celeb® 250/450/450Q



Celeb® 250, 450 and 450Q LED's have four menu options, one white, two colors and **FX**. In the white menu, the Kelvin range is from 2700K to 6500K with **Dimming, Kelvin** and **Green/Magenta** control channels. In the first color menu, Kelvin range is from 2500K to 9900K, with three additional channels, **Gel, Hue Angle** and **Saturation**. The Gel channel includes Kino Flo presets and over 100 well-known lighting gels. The second color menu provides individual **RGB** (red, green, blue) control. The **FX** (Effects) menu has custom presets like Candle, Fire, TV, Police, Lightning, Paparazzi, Pulse and Scroll.

Kino Flo's Celeb LED family also comes with standard DMX and wireless DMX (Lumen Radio®), universal voltage input 100-240VAC and 24VDC input (Celeb 250). SnapBag Softbox and SnapGrid accessories are also available.

Features include:

- Tunable Kelvin 2500K to 9900K
- Dimming without color shift
- Green/Magenta control
- Kino Flo presets and Gel presets
- Dial-in color using Hue angle and Saturation control
- RGB control
- FX (Effects) control
- Universal input 100-240VAC
- Manual and DMX dimming w/ Auto Terminate
- DMX wireless (Lumen Radio)

▼ Celeb 250 LED DMX Center



CEL-250CU
Celeb 250 LED DMX
Center Mount, Univ



LVR-CE290-P
Celeb 250
Louver/HP, 90°
(Included)



MTP-LBC
Kino 41 Lollipop w/
Baby Receiver Curve
(16mm) (Included)

▼ Celeb 250 LED DMX Yoke



CEL-250YU
Celeb 250 LED DMX
Yoke Mount, Univ



CEL-250PU
Celeb 250 LED DMX
Pole-Op, Univ



LVR-CE290-P
Celeb 250 Louver/HP, 90°
(Included)

▼ Celeb 450 LED DMX Center



CEL-450CU
Celeb 450 LED DMX
Center Mount, Univ



LVR-CE490-P
Celeb 450 Louver/HP, 90°
(Included)



MTP-LM
Kino 81 Lollipop w/
Junior Pin (28mm)
(Included)

▼ Celeb 450 LED DMX Yoke



CEL-450YU
Celeb 450 LED DMX
Yoke Mount, Univ



CEL-450PU
Celeb 450 LED DMX
Pole-Op, Univ



LVR-CE490-P
Celeb 450 Louver/HP, 90°
(Included)

Celeb® 250/450/450Q

▼ Photometrics

Celeb 250

FC	695	185	84	48	31	22	16	12	10	8
Feet	2	4	6	8	10	12	14	16	18	20
LUX	10300	2990	1340	763	488	340	255	198	158	131
Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

Celeb 450

FC	955	316	155	91	59	42	32	24	20	16
Feet	2	4	6	8	10	12	14	16	18	20
LUX	13200	4860	2370	1420	930	655	490	383	311	255
Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

Celeb 450Q

FC	1160	355	167	96	63	44	33	26	21	17
Feet	2	4	6	8	10	12	14	16	18	20
LUX	16800	5600	2610	1530	991	696	517	404	325	267
Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ Fixture Specifications

Fixture	Input Voltage VAC	Amps VAC	Input Voltage VDC	Amps 24VDC	Kelvin Range	Dimming Range	Dimensions	Weight
Celeb 250 DMX Center	100-240VAC, 50/60Hz, 145W	1.2A 0.7A	18-36VDC, 150W	6.25A	2500-9900	100%-1%	24 x 5 x 14" (61 x 13 x 35.5cm)	15 lb (7kg)
Celeb 250 DMX Yoke	100-240VAC, 50/60Hz, 145W	1.2A 0.7A	18-36VDC, 150W	6.25A	2500-9900	100%-1%	28.5 x 5 x 16.5" (72 x 13 x 42cm)	16 lb (7.5kg)

▼ Fixture Specifications

Fixture	Input Voltage VAC	Amps VAC	Kelvin Range	Dimming Range	Dimensions	Weight
Celeb 450 DMX Center	100-240VAC, 50/60Hz, 255W	2.5A 1.1A	2500-9900	100%-1%	45 x 5 x 14" (114.5 x 13 x 36cm)	26 lb (12kg)
Celeb 450 DMX Yoke	100-240VAC, 50/60Hz, 255W	2.5A 1.1A	2500-9900	100%-1%	50 x 5 x 16.5" (127 x 13 x 42cm)	26 lb (12kg)

▼ Fixture Specifications

Fixture	Input Voltage VAC	Amps VAC	Kelvin Range	Dimming Range	Dimensions	Weight
Celeb 450Q DMX Yoke	100-240VAC, 50/60Hz, 270W	2.7A 1.1A	2500-9900	100%-1%	30 x 5 x 26" (76 x 13 x 66cm)	24 lb (11kg)

▼ Details




▼ Celeb 450Q LED DMX Yoke



CEL-450QU
Celeb 450Q LED DMX Yoke Mount, Univ



CEL-450QPU
Celeb 450Q LED DMX Pole-Op, Univ



LVR-CE490-QP
Celeb 450Q Louver/HP, 90° (Included)

▼ Accessories



BRD-CE4
Celeb 450 Barndoors (Set of 4)
BRD-CE4-Q
Celeb 450Q Barndoors (Set of 4)
BRD-CE2
Celeb 250 Barndoors (Set of 4)



LVR-CE460-P
Celeb 450 Louver/HP, 60°
LVR-CE460-QP
Celeb 450Q Louver/HP, 60°
LVR-CE260-P
Celeb 250 Louver/HP, 60°



DFS-CE200-S
Celeb 250 SnapBag w/ 2 x Diffusion
DFS-CE400-S
Celeb 450 SnapBag w/ 2 x Diffusion
DFS-CE400Q-S
Celeb 450Q SnapBag w/ 2 x Diffusion



LVR-FS240-S
Celeb 250 SnapGrid 40°
LVR-CE440-S
Celeb 450 SnapGrid 40°
LVR-CE440Q-S
Celeb 450Q SnapGrid 40°



MTP-180
Junior Pin Assembly for Yoke (28mm)



MTP-140
Baby Receiver Assembly for Yoke (16mm)

Celeb® 250/450/450Q

▼ Celeb 250 LED DMX Kits



KIT-C250U

Celeb 250 LED DMX Center Mount Kit, Univ

Contents	Dimensions
1 Celeb 250 LED DMX Center	29 x 10.5 x 17"
1 Flight Case	(74 x 27 x 43cm)
	Weight
	31 lb (14kg)



KIT-C250YU

Celeb 250 LED DMX Yoke Mount Kit, Univ

Contents	Dimensions
1 Celeb 250 LED DMX Yoke	32.5 x 8.5 x 24"
1 Jr. Pin	(83 x 22 x 61cm)
1 Ship Case	Weight
	40 lb (18kg)

▼ Celeb 450/450Q LED DMX Kits



KIT-C450U

Celeb 450 LED DMX Center Mount Kit, Univ

Contents	Dimensions
1 Celeb 450 LED DMX Center	53.5 x 11 x 16.5"
1 Flight Case	(136 x 28 x 42cm)
	Weight
	52.5 lb (24kg)



KIT-C450YU

Celeb 450 LED DMX Yoke Mount Kit, Univ

Contents	Dimensions
1 Celeb 450 LED DMX Yoke	54.5 x 9.5 x 25"
1 Jr. Pin	(138.5 x 24 x 63.5cm)
1 Ship Case	Weight
	57 lb (26kg)



KIT-C450QU

Celeb 450Q LED DMX Yoke Mount Kit, Univ

Contents	Dimensions
1 Celeb 450Q LED DMX Yoke	34.5 x 8.5 x 33"
1 Jr. Pin	(88 x 22 x 84cm)
1 Ship Case	Weight
	52 lb (24kg)

▼ Cases



KAS-CE2
Celeb 250
Center Flight Case



KAS-CE2-Y
Celeb 250
Yoke Ship Case



KAS-CE4-Q
Celeb 450Q
Yoke Ship Case



KAS-CE4
Celeb 450
Center Flight Case



KAS-CE4-Y
Celeb 450
Yoke Ship Case



Kino Flo Lighting Systems
2840 North Hollywood Way
Burbank, CA 91505

+1 818 767 6528 voice +1 818 767 7517 fax

www.kinoflo.com
©Kino Flo Celeb 250/450/450Q
No. 3110099 Rev D