

FreeStyle 41

FreeStyle 41 LED DMX



reeStyle LED has four menu options, one white, two colors and FX. With white light Kelvin range is from 2700K to 6500K with **Dimming**, **Kelvin** and **Green/Magenta** control channels. In the first color menu, Kelvin range is from 2500K to 9900K, with three additional channels, **Gel**, **Hue Angle** and **Saturation**. The Gel channel includes Kino Flo presets such as blue & green screen and over 100 well-known lighting gels. The second color menu provides individual **RGB** (red, green, blue) control. The **FX** (Effects) menu has custom presets like Candle, Fire, TV, Police, Lightning, Paparazzi, Pulse and Scroll. For additional versatility, the FreeStyle LED panel can be easily removed from the housing and mounted onto a stand. The Gaffer Tray accessory allows further flexibility with its slim profile and center mount and screw points. The controller comes with standard DMX, wireless DMX (Lumen Radio®), universal voltage input 100-240VAC and 24VDC. It can operate remotely with a 25ft extension cable or can be mounted to the Gaffer Tray.

Features include:

- Kelvin presets & custom settings, 2500K-9900K
- · Dimming without color shift
- Green/Magenta control
- Dial in any color through Hue Angle and Saturation control
- Kino Flo presets and Gels
- RGB control
- FX (Effects) control
- Manual & DMX Dimming, DMX wireless (Lumen Radio)
- Removable fixture includes built-in Barndoors, Honeycomb Louver
- Twist-on, locking Center Mount and corner mount options

▼ FreeStyle 41 LED DMX System

CFX-F41 FreeStyle 41 LED Fixture





LED-152X-230U FreeStyle 152 LED DMX Controller, Univ 230U



MTP-BG41 KinoGrip 41K Mount w/ Baby Receiver (16mm)



X12-25 FreeStyle Extension, 25ft

Photometrics

FreeStyle 41 FC FreeStyle 41 2500-91 FreeStyle 51 100-2401/4C, 100/60H2, 150W ▼ Details FF FreeStyle 51/2 100-2401/4C, 100/60H2, 150W ▼ Details FF FreeStyle 51/2 100-2401/4C, 100/60H2, 150W ▼ Details Image: 100 - 2401/4C, 100	ef 2 X 64 eters 0 iccatic 900 900 900 900 900	2 6840 2 0.5 0ns Dimming 100%~ 100%~ 100%~	-1% 5 (1) -1% 5 (1) -1% 4 (1) cations Voltage Amps 24VD	2.5 x 4 33 x 10 0 x 2.5 z 4 27 x 6. 27 x 6. 26 x 6.5 26 x 6.5	10 2 462 2.5 5 5 x 9" w/ 6) x 23cm w x 8" 5 x 20cm) .5 x 7.5" 5 x 19cm) Range	21 1 12 325 3 " barndoor // 15cm b Dimming Ran 100%~1%	arndoors) nge Dime	4	18 53 1 4.5 16 lt (7kg) 12.5 (6kg) 10 lb (4.5kg	lb	 	SYS-F4 FreeSty Content 1 Free 1 Free 1 MTP- 1 Exte	le 41 s Style 4 Style 1 BG41
FreeStyle 41 LUX ▼ Fixture Specifi Intervention FreeStyle 41 2500-91 FreeStyle 41 2500-91 FreeStyle 41 2500-91 FreeStyle 41 2500-91 Panel 41 Only 2500-92 V LED Controller Intervention VLED Controller Intervention VLED Controller Intervention VIC: Value 100-240VAC, 50/60Hz, 1500 V Details FreeStyle FreeStyle Intervention Image: Style 5 (Style 5 (Styl	X 68 eters 0 icctic 900 900 900 900 900	6840 2 0.5 0ns Dimming 100%- 100%- 100%- s s	4 6 2450 121 1 1.5 g Range D -1% 5 -1% 5 -1% 5 -1% 5 Voltage Arros 24YD 24YD	8 0 712 1 2 1 1 1 2 1 2 2 3 3 1 0 0 2.5 x 4 33 x 10 0 0 x 2.5 2 27 x 6.5 9.5 x 2. 26 x 6.5 27 x 6.5 26 x 6.5 27 x 6.5 26 x 6.5 27	10 2 462 1 2.5 5 x 9" w/ 6) x 23cm w x 8" 5 x 20cm) 5 x 7.5" 5 x 19cm) Range	12 325 3 " barndoor // 15cm b	14 242 1 3.5 "s arndoors)	16 189 1 4	18 53 1 4.5 16 lt (7kg) 12.5 (6kg) 10 lb (4.5kg	20 123 15 10 10 10 10 10 10 10 10 10 10 10 10 10	 	FreeSty Content 1 Free 1 Free 1 MTP	le 41 s Style 4 Style 1 BG41
▼ Fixture Specifi FreeStyle 41 2500-93 FreeStyle 61 41 2500-93 Panel 41 Only 2500-93 ▼ LED Controlle Input Voltage Controller Input Voltage LED-152X 100-240VAC, 50/60HZ, 150W ▼ Details Imput Voltage Imput Voltage Imput Vo	eters 0 icatic 990 900 900 900 900 900 900	0.5 ONS Dimming 100%- 100%- 100%- 100%- s Input \	I I 1 1.5 g Range D -1% 5 -1% 5 -1% 5 -1% 4 -1% 4 Voltage Amps	2.5 x 4 33 x 10 0 x 2.5 z 4 27 x 6. 27 x 6. 26 x 6.5 26 x 6.5	2.5 x 9" w/ 6 0 x 23cm w x 8" 5 x 20cm) 5 x 7.5" 5 x 19cm) Range	" barndoor // 15cm b	3.5 rs arndoors)	4 ···	Weigh 16 lt (7kg) 12.5 (6kg) 10 lb (4.5kt	1 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	 	FreeSty Content 1 Free 1 Free 1 MTP	le 41 s Style 4 Style 1 BG41
▼ Fixture Specifi itature Kelvin Ran creeStyle 41 2500-91 creeStyle/GT 41 2500-91 creeStyle/GT 41 2500-91 Panel 41 Only 2500-91 Controller Input Voltage ED152X 100-240VAC, 50/60Hz, 150W ▼ Details ED152X FreeStyle ED152X 0 0 0 Details	icatic 1990 900 900 900 €r Sp Amps VAC	ons Dimming 100%- 100%- 100%- secific vyc	g Range D -1% 5 -1% 5 -1% 5 -1% 5 -1% 4 -1% 4 -1% 2 Voltage Arros 24VD 24VD	imensions 2.5 x 4 33 x 10 0 x 2.5 27 x 6.1 9.5 x 2. 26 x 6.5 x 6.5	s x 9" w/ 6) x 23cm w x 8" 5 x 20cm) 5 x 7.5" 5 x 19cm) Range	" barndoor // 15cm b Dimming Rar	rs arndoors) nge Dime	4 ·	Weight 16 lb (7kg) 12.5 (6kg) 10 lb (4.5kg	lb j) Weight	 	FreeSty Content 1 Free 1 Free 1 MTP	le 41 s Style 4 Style 1 BG41
itature Kelvin Ran ireeStyle 41 2500-91 ireeStyle/GT 41 2500-91 Panel 41 Only 2500-93 ▼ LED Controller Outroller NVC ▼ Details	nge 900 900 900 900 ≥r Sp Amps VAC	Dimming 100%~ 100%~ 100%~ pecific s Input \	-1% 5 (1) -1% 5 (1) -1% 4 (1) cations Voltage Amps 24VD	2.5 x 4 33 x 10 0 x 2.5 27 x 6.1 9.5 x 2. 26 x 6.5 Kolvin	x 9" w/ 6) x 23cm w x 8" 5 x 20cm) .5 x 7.5" 5 x 19cm) Range	ı/ 15cm b Dimming Rat	arndoors) nge Dime	ensions	16 lb (7kg) 12.5 (6kg) 10 lb (4.5kg	j) Weight	 	FreeSty Content 1 Free 1 Free 1 MTP	le 41 s Style 4 Style 1 BG41
FreeStyle 41 2500-94 FreeStyle / GT 41 2500-94 Panel 41 Only 2500-95 ▼ LED Controller Input Voltage Controller Input Voltage IED-152X 100-240VAC, 50/60Hz, 150W ▼ Details Imput Voltage Imput Voltage	900 900 900 900 er Sp <u>Amps</u>	100%~ 100%~ 100%~ pecific s Input \	-1% 5 (1) -1% 5 (1) -1% 4 (1) cations Voltage Amps 24VD	2.5 x 4 33 x 10 0 x 2.5 27 x 6.1 9.5 x 2. 26 x 6.5 Kolvin	x 9" w/ 6) x 23cm w x 8" 5 x 20cm) .5 x 7.5" 5 x 19cm) Range	ı/ 15cm b Dimming Rat	arndoors) nge Dime	ensions	16 lb (7kg) 12.5 (6kg) 10 lb (4.5kg	j) Weight	 	FreeSty Content 1 Free 1 Free 1 MTP	le 41 s Style 4 Style 1 BG41
reeStyle/GT 41 2500-94 Panel 41 Only 2500-95 ▼ LED Controller antroller Input Voltage ED152X 100-240VAC, 50/60Hz, 150W ▼ Details FreeStyle	900 900 er Sp Amps VAC	100%~ 100%~ pecific s Input \	(1) -1% 5 (1) -1% 4 (1) cations Voltage Amps 24VD	33 x 10 0 x 2.5 27 x 6.5 9.5 x 2. 26 x 6.5 c Kelvin) x 23cm w x 8" 5 x 20cm) 5 x 7.5" 5 x 19cm) Range	ı/ 15cm b Dimming Rat	arndoors) nge Dime	ensions	(7kg) 12.5 (6kg) 10 lb (4.5kg	ıb j) Weight 4 Ib	 	FreeSty Content 1 Free 1 Free 1 MTP	le 41 s Style 4 Style 1 BG41
Panel 41 Only 2500-93 ▼ LED Controlle Controller Input Voltage ED-152X 100-240VAC, 50/60Hz, 150W ▼ Details FreeStyle	900 er Sp Amps VAC	100%~ pecific s Input \ VDC	(1) -1% 4 (1) cations Voltage Amps 24VD	27 x 6. 9.5 x 2. 26 x 6.5	5 x 20cm) .5 x 7.5" 5 x 19cm) Range				(6kg) 10 lb (4.5k	j) Weight 4 lb	 	1 Free 1 Free 1 MTP-	Style 4 Style 1 BG41
✓ LED Controlle controller V/C ED-152X 100-240VAC, 50/60Hz, 150W ✓ Details ✓ Details	er Sp Amps VAC	oecific s Input \ VDC	-1% 4 (1) cations Voltage Amps 24VD	9.5 x 2. 26 x 6.5 Kelvin	.5 x 7.5" 5 x 19cm) Range				10 lb (4.5k) Weight 4 lb	 	1 Free 1 MTP	Style 1 BG41
Controller nput Voltage V4C ED-152X 100-240VAC, 50/60Hz, 150W ▼ Details ▼ Details FreeStyle	Amps VAC	s Input \ VDC	cations Voltage Amps 24VD	C Kelvin	Range					Weight 4 lb	 	1 MTP	BG41
Controller V4C ED-152X 100-240VAC, 50/60Hz, 150W ▼ Details FreeStyle	Amps VAC	s Input \ VDC	Voltage Amps 24VD						.m)	4 lb	 	1 Exte	nsion,
ED-152X 100-240VAC, 50/60Hz, 150W ▼ Details FreeStyle									:m)	4 lb			
▼ Details	1.25A 0.65/		6.25	A 2500)~9900	100%~1%	(38)	x 4.5 x 3″ x 11.5 x 8d	:m)	4 lb (2kg)			
FreeStyle					1	C							
FreeStyle					*	C			_				
		Ó				25				0		SYS-F4 FreeSty Content 1 Free! 1 MTP- 1 Exter	le/GT s Style/ Style 1 BG41
	SYS-	S-BK12						DFS - FS4			2		
	Syste		Single Batt OWhr, 28.8\ /)		L	T		FreeSty w/ 2x			1		
and the			1 Fixture She	<u>) </u>				LVR-FS4 FreeSty		SnapGrid, 40			
≈ 1 0 ₪ 1	FIX-F Free!							LVR-SL4	90-P le 41 L		BI		•

▼ FreeStyle 41 LED DMX Systems



LED DMX System, Univ

- 41 LED Fixture
- 152 LED DMX Controller
- Mount w/ Baby Receiver (16mm)
- 25ft



41 LED DMX System, Univ

- GT 41 LED Fixture
- 52 LED DMX Controller
- Mount w/ Baby Receiver (16mm)
- 25ft







MTP-BG41S KinoGrip 41K Mount w/

Baby Receiver Short (16mm)

MTP-B41F Kino Offset w/ Baby Receiver (16mm)



FreeStyle 41 LED DMX Kits

Dimensions 54.5 x 9 x 21"

Weight

49 lb

(22.5kg)

(138.5 x 23 x 53.5cm)

▼ FreeStyle 41 LED DMX Kits



KIT-F41U

FreeStyle 41 LED DMX Kit, Univ w/ Travel Case

Contents	

1 FreeStyle 41 LED Fixture

1 FreeStyle 152 LED DMX Controller

1 MTP-BG41 Mount w/ Baby Receiver (16mm)

-tr 1 (1011111)

- 1 Extension, 25ft 1 Travel Case
- i ilavoi cuso



KIT-F41TU

FreeStyle/GT 41 LED DMX Kit, Univ w/ Travel Case

ontents	Dimensions				
FreeStyle/GT 41 LED Fixture	54.5 x 9 x 21″				
FreeStyle 152 LED DMX Controller	(138.5 x 23 x 53.5cm)				
Baby Receiver (16mm)	Weight				
Extension, 25ft	46 lb				
Travel Case	(21kg)				
	FreeStyle/GT 41 LED Fixture FreeStyle 152 LED DMX Controller MTP-BG41 Mount w/ Baby Receiver (16mm) Extension, 25ft Travel Case				



Kino Flo Lighting Systems 2840 North Hollywood Way Burbank, CA 91505 +1 818 767 6528 voice +1 818 767 7517 fax

WWW.kinoflo.com © Kino Flo FreeStyle 41 No. 3110115 Rev B